

Rated Voltage(V)	Category Voltage(V)	Surge Voltage(V)	Nominal Capacitance (μF)	tg δ (%)	ESR (Ω) 1kHz	Leakage Current max(μA)		Impedance max (Ω) 100Hz	Capacitance Variation(%)		Dimension D X H (mm)	Max Weight (g)
						25℃	85℃ 125℃	-55℃	-55℃	85℃		
10	6	11	100000	180	0.035	300	1800	1	-80	160	36×12	93
			150000		0.025						36×16	118
16	9.5	17.6	60000	165	0.035	300	1800	1	-80	160	36×12	93
			90000		0.025						36×16	118
25	15	27.5	36000	130	0.04	300	1800	1	-75	160	36×12	93
			54000		0.035						36×16	118
35	20	38.5	24000	95	0.04	300	1800	1	-70	160	36×12	93
			36000		0.035						36×16	118
50	30	55	11000	65	0.1	300	2400	1.2	-60	120	36×10	76
			12000	65	0.1	300	2400		-60	120	36×12	93
			16000	70	0.04	400	2400		-55	135	36×12	93
			18000	70	0.04	400	2400		-55	135	36×12	93
			24000	70	0.035	400	2400		-55	135	36×16	118
63	38	70	8000	50	0.04	400	2400	1.4	-45	90	36×12	93
			12000		0.035						36×16	118
80	48	88	5600	40	0.06	500	3000	1.6	-40	90	36×12	95
			8200		0.04						36×16	118